

# PicSight G43AB-GigE-AS

GigE Vision camera



## Technical specifications

Interface	Ethernet 1000/100/10 Mb/s
Sensor	1/3" CMOS, parallel readout, type Aptina MT9V033
Spectral sensitivity	<p>The graph shows the quantum efficiency of the sensor across a range of wavelengths from 350 nm to 1050 nm. The Blue channel (solid blue line) peaks at approximately 450 nm. The Green (B) channel (dotted green line) peaks at approximately 500 nm. The Green (R) channel (dashed green line) peaks at approximately 650 nm. The Red channel (solid red line) peaks at approximately 700 nm. The efficiency for all channels drops significantly after 850 nm.</p>
Monochrome/color	bayer pattern
Output image resolution (H×V)	752 × 480 pixels
Frame rate	64 fps
Video format	10-bit, single tap
Scanning	progressive
Pixel size (H×V)	6 × 6 μm
Sensor size (H×V)	4.512 × 2.88 mm
Shutter	global, 10 μs –1000 ms (default 15 ms)
Operating (trigger) modes	<ul style="list-style-type: none"> <li>• Free running</li> <li>• Triggered mode</li> </ul>
Gain & black level	<ul style="list-style-type: none"> <li>• Analog gain: 0 .. 12.04 dB (default 12 dB)</li> <li>• Digital gain: -12.04 .. 11.48 dB (default 0 dB)</li> <li>• Black level: 0 .. 6.35 DN (default 0 DN)</li> </ul>
Auto functions	<ul style="list-style-type: none"> <li>• Auto exposure</li> <li>• Automatic analog gain control</li> <li>• Automatic black level</li> </ul>
Area of interest (AOI)	Horizontal and vertical AOI applicable directly at the sensor
Binning	• n/a
Decimation	• n/a
Mount	C-mount (CS-mount on request)
Dimension	<ul style="list-style-type: none"> <li>• 44.8×31.4×91.7 mm (W×H×L, without connectors) — standard version</li> <li>• 44.8×37.56×96.0 mm (W×H×L, without connectors) — right angle version</li> </ul>
Weight	145 g
Power input	10-26V/5W

## Ordering information

Ordering number	Product name	Option
413202	PicSight G43AB-GigE-AS	Hirose/SDR-26 connector
413203	PicSight G43AB-GigE-AS-H	Hirose/SDR-26 connector, 90° lens mount
413227	PicSight G43AB-GigE-PoE-S	PoE, Hirose/SDR-26 connector
413228	PicSight G43AB-GigE-PoE-S-H	PoE, Hirose/SDR-26 connector, 90° lens mount
413302	PicSight G43AB-GigE-AS-RTF	Realtime function, lens controller, Hirose/SDR-26 connector
413303	PicSight G43AB-GigE-AS-RTF-H	Realtime function, lens controller, Hirose/SDR-26 connector, 90° lens mount
413327	PicSight G43AB-GigE-PoE-S-RTF	PoE, Realtime function, lens controller, Hirose/SDR-26 connector
413328	PicSight G43AB-GigE-PoE-S-RTF-H	PoE, Realtime function, lens controller, Hirose/SDR-26 connector, 90° lens mount

Check latest price list or contact us to learn if more options are available.

**Headquarters (Switzerland)**  
 Leutron Vision AG  
 Industriestrasse 57  
 CH-8152 Glattbrugg, Switzerland  
 Phone ++41 44 809 88 22  
 fax ++41 44 809 88 29  
 intsales@leutron.com  
[www.leutron.com](http://www.leutron.com)

**Germany**  
 Leutron Vision GmbH  
 Macairestrasse 3  
 D-78467 Konstanz, Germany  
 Phone ++49 7531 5942 0  
 fax ++49 7531 594299  
 desales@leutron.com  
[>www.leutron.com/de/](http://www.leutron.com/de/)

**North America**  
 Leutron Vision Inc.  
 38 East Street  
 Halifax, MA 02338, USA  
 Phone: ++1 888 442 2269 x1  
 Fax: ++1 781 353 3943  
 ussales@leutron.com  
[www.leutron.com/](http://www.leutron.com/)

**Czech Republic**  
 Leutron Vision s.r.o.  
 Rokycanska 27  
 31200 Plzen, Czech Republic  
 Phone: ++420 377 260 342  
 czsales@leutron.com  
[www.leutron.com/](http://www.leutron.com/)