

# PicSight P32M-Smart502

Smart GigE camera



Technical specifications	
Interface	Ethernet 1000/100/10 Mb/s
Smart technology	32-bit RISC processor PNX0192/300MHz, 64MB RAM, 32MB Flash memory, real-time operating system, C/C++ compiler, various APIs
Sensor	1/2" CCD, interline transfer, type SONY ICX414
Spectral sensitivity	
Monochrome/color	monochrome
Output image resolution (H×V)	656 × 494 pixels
Full sensor resolution (incl. black pixels)	692 × 504 pixels
Frame rate	62 fps
Video format	12-bit, single tap
Scanning	progressive
Pixel size (H×V)	9.9 × 9.9 μm
Sensor size (H×V)	7.48 × 6.15 mm
Shutter	global, 5 μs –60000 ms (default 16 ms)
Operating (trigger) modes	<ul style="list-style-type: none"> <li>• Free running</li> <li>• Triggered mode</li> <li>• Long range exposure mode</li> </ul>
Gain & black level	<ul style="list-style-type: none"> <li>• Analog gain: -6 .. 30 dB (default 4 dB)</li> <li>• Digital gain: n/a</li> <li>• Black level: 0 .. 25.5 DN (default 0 DN)</li> </ul>
Auto functions	• n/a
Area of interest (AOI)	Vertical AOI applicable directly at the sensor
Binning	• Vertical: 2×
Decimation	• n/a
Mount	C-mount (CS-mount on request)
Dimension	<ul style="list-style-type: none"> <li>• 44.8×31.4×91.7 mm (W×H×L, without connectors) — standard version</li> <li>• 44.8×37.56×96.0 mm (W×H×L, without connectors) — right angle version</li> </ul>
Weight	145 g
Power input	10-26V/5W

## Ordering information

Ordering number	Product name	Option
120602	PicSight P32M-Smart502-AS	PNX1502, 300MHz, 64MB-DDR, lens controller, Hirose/SDR-26 connector
120603	PicSight P32M-Smart502-AS-H	PNX1502, 300MHz, 64MB-DDR, lens controller, Hirose/SDR-26 connector, 90° lens mount
120627	PicSight P32M-Smart502-PoE-S	PoE, PNX1502, 300MHz, 64MB-DDR, lens controller, Hirose/SDR-26 connector
120628	PicSight P32M-Smart502-PoE-S-H	PoE, PNX1502, 300MHz, 64MB-DDR, lens controller, Hirose/SDR-26 connector, 90° lens mount

Check latest price list or contact us to learn if more options are available.

**Headquarters (Switzerland)**  
 Leutron Vision AG  
 Industriestrasse 57  
 CH-8152 Glattbrugg, Switzerland  
 Phone ++41 44 809 88 22  
 fax ++41 44 809 88 29  
 intsales@leutron.com  
[www.leutron.com](http://www.leutron.com)

**Germany**  
 Leutron Vision GmbH  
 Macairestrasse 3  
 D-78467 Konstanz, Germany  
 Phone ++49 7531 5942 0  
 fax ++49 7531 594299  
 desales@leutron.com  
[>www.leutron.com/de/](http://www.leutron.com/de/)

**North America**  
 Leutron Vision Inc.  
 38 East Street  
 Halifax, MA 02338, USA  
 Phone: ++1 888 442 2269 x1  
 Fax: ++1 781 353 3943  
 ussales@leutron.com  
[www.leutron.com/](http://www.leutron.com/)

**Czech Republic**  
 Leutron Vision s.r.o.  
 Rokycanska 27  
 31200 Plzen, Czech Republic  
 Phone: ++420 377 260 342  
 czsales@leutron.com  
[www.leutron.com/](http://www.leutron.com/)